

# SPECIALTY SEAL™

Specialty Seal™ products are designed for specific purposes and can be used on a variety of surface materials. They provide superior results for distinct outcomes, such as stain prevention and protection for counter tops or natural stone.

## Specialty Seal™ Products:

- PRX Paver Restore X-treme™
- JS Joint Stabilizer™
- 2PX Two Part X-treme™
- SGX Stain Guard X-treme™
- CG Counter Guard™
- S-PS Stone Penetrating™
- S-PSX Stone Penetrating X-treme™



# SEALING ACCESSORIES



## SRW Slit Foam Rollers

SRW Slit Foam Rollers are a must-use product when sealing. They help ensure an even application.



## SRW Sealer Sprayers

Sprayers help evenly apply the sealer to the hardscape surface. Try one of our high-quality sealer sprayers!



## General Cleaners

The best seal starts with a clean surface, and each hardscape surface has distinctly different qualities. SRW has the cleaner that's right for the job.



Distributed by:

SRWProducts.com | 800-752-9326



# PRX PAVER RESTORE X-TREME™



SRWProducts.com • 800-752-9326

# PRX Paver Restore X-treme™



Restore old paver surfaces and add rich color with this pigmented sealer. The color reviving technology makes old pavers look new again by evening out irregularities among older pavers.

## Applications

- ▶ Concrete Pavers
- ▶ Projects include:
  - ▶ Driveways
  - ▶ Patios/Walkouts
  - ▶ Pool Decks
  - ▶ Exposed aggregate concrete
  - ▶ Stamped Concrete

## Benefits

- ▶ Restores faded pavers with color reviving technology
- ▶ High gloss, wet look, restoring pigmented sealer
- ▶ Highlights and preserves the natural pigments in the surface
- ▶ Percolates around exposed aggregate to even out irregularities and adds rich color
- ▶ Highly durable, long lasting protection for extreme conditions
- ▶ Recommended for driveways & commercial applications
- ▶ Provides superior protection against freeze/thaw cycles, deicing salts, and chemical erosion and efflorescence
- ▶ Designed for exterior use

## COLOR REVIVING TECHNOLOGY



PRX is a pigmented sealer which helps smooth out variations in the paver surface. After years of use, pavers begin to show their aggregate, irregularities, and fade from exposure to the elements. PRX can turn your project around and give it a fresh look like it was just installed!

## 5 YEAR OLD PATIO BEFORE PRX



## 5 YEAR OLD PATIO AFTER PRX



## EASY 4-STEP PROCESS

### 1. CLEAN

- Wait 28 days after installing polymeric sand before sealing.
- Thoroughly sweep surface of joint sand or loose material.
- Spot clean if needed with one of the SRW Specialty Clean™ products. Then prepare surface with an SRW Products General Purpose Cleaner.

### 2. CLIMATE

- After cleaning, wait at least 24 hours before sealing. Surface and joints must be completely dry.
- Recommended application temperatures are 50°F - 80°F (10°C - 27°C) from installation through the cure process.
- Do not apply if inclement weather is forecasted within 24 hours.

### 3. APPLY

- **STIR THOROUGHLY. Be sure to stir prior to and during use. Due to pigment, product should be blended every 20 minutes.**
- Apply with an SRW Products approved Slit Foam Roller and sprayer.
- For best results, spray then back roll. This prevents an uneven finish. A 2-person application is recommended.
- Start at the highest project elevation. Do not allow sealer to pool on surface or in joints.
- Repeat if desired.

### 4. CURE

- Protect from moisture & allow sealed area to dry and cure at least 24 hrs.
- Low temps and high humidity may extend dry time
- Dry-tack free: 60 min. | Foot traffic: 24 hrs. | Vehicle traffic: 48 hrs.

Note: all calculations based on 68°F - 77°F (20°C - 25°C)



For more information visit  
**SRWProducts.com**